Technical data sheet

Corospin 513

Tile clip

Tile clip made of stainless steel for cut tiles. It enables fast and stable fixing of the tiles to the roof battens.

Advantages

- protects tiles against slipping out
- an easy and stable ridge tile fixing
- protects againts unfavourable wind influence

Application

 for the fixing of roofing clips and cut tiles in baskets and corners

Characteristics

Material	stainless steel	Dimensions of the plate	17x19x23 mm
Colour	steel	Clamping plate thickness	≥1,0 mm
Wire size	0,8 mm	Mechanical strength	≥ 0,15 kN
Wire length	400 mm		

The product has passed a positive assessment of its performance for the intended use: fixing of roofing elements. Confirmation document: National Technical Assessment No. ITB-KOT-2020/1307 edition 1.

Installation

1. Tiles should be placed on battens.

2. The lath on the underside of the tile is covered with a clamp so that the hooks on the wire are pointing towards the tile to be fixed.

Storage

The product should be stored in dry and covered areas, protected from deformation. Transport in covered means of transport, adequately protecting against damage.

Packaging

Quantity per box (pcs.):	25
Quantity on a pallet (pcs):	20000

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.



