

Product sheet

Basic Information

Order Number
Type
Common Number

2309010010
UTP CAT5E PVC
S9121




8595025319302



Measuring Unit
Packaging
Net Weight [kg]
Dimensions [mm]
Technical Support

M
305 / - / - / 305
9.505
360 × 220 × 360
Petr Veselý, 581261172,
vesely@emos.cz



Basic Product Description

Unshielded horizontal cable of the highest quality, category CAT5E with PVC jacket. The cores of conductors are made of non-recycled copper. The cable meets the requirements of the construction products regulation (CPR).

Technical Description

warranty period	10 years
product type	UTP cable without connectors
length	UTP CAT 5E PVC
cable structure	305 m
category	wire
material of the inner conductor	5E
AWG	copper (Cu)
inner conductor diameter	24
wire insulation	0.51 mm
conductor insulation thickness	HDPE
strength member	0.22 mm
	Nylon 150D

Product sheet

cable sheath	PVC
jacket diameter	5.2 mm
jacket thickness	1.1 mm
sheath color	grey (RAL 7035)
marking of cable	UTP Cat5E PVC 1 – 305 m
highest supported protocol	1000 Base-T (Gigabit Ethernet)
storage temperature	-20 °C to +60 °C
mounting temperature	+5 °C to +60 °C
maximum operating humidity	93 %
reaction to the fire	Eca
dangerous substances	none
number of wires	8
packaging	305 m, paper box