



**Technical Characteristic KAI/KOS
FISA TEHNICA**

ODU
16.07.05(7/0)

**Model White "CELINE"
Internal code: 4694;4693;4695;2880
Type: Ceramic Wall Tiles
Group BIII, 300x 600x 9 mm**

Characteristics Group BIII, Annex L	Tolerance EN 14411:2016, %	Tolerance EN14411:2016, mm	Request values/Valori conform standard	Measured in KAI laboratory/Masuratori in laborator Kai	Testing method/Metoda de lucru
1. Length/width Lungime/Latime, mm	±0.5/max±2mm	±1.50/±2.00	±1.30/±1.80	300.0 – 300.3 600.0 – 600.3	EN ISO 10545-2
2.Thickness Grosimea, mm	±10/max±0.5mm	±0.50	± 0.5 mm	9.1 – 9.2	EN ISO 10545-2
3. Surface quality Calitatea suprafetei	≥95% without defects	≥95% without defects	≥98% without defects	Pass	EN ISO 10545-2
4.Water absorption Absorbția de apa, %	Fb>10%	Eb>10%	Eb>10%	14.90 16.30 %	EN ISO 10545-3
5.Modulus of rupture Rezistența mecanică, N/mm ²	≥12 N/mm ²	≥12 N/mm ²	≥12 N/mm ²	Average: 24 N/mm ²	EN ISO 10545-4
6. Breaking strength Forța de rupere, N	≥ 600 N	≥ 600 N	≥ 600 N	Average: 1038 N	EN ISO 10545-4
7.Crazing resistance, glazed tiles/Resistența la crapături pentru placi glazurate	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	EN ISO 10545-11
8.Resistance for household chemicals and swimming pool salts/Rezistența la soluțiile de uz casnic și saruri de piscină	Min class B	Min class B	Min class B	GA	EN ISO 10545-13
9.Resistance to the low concentration acids and alkalis/Rezistența la acizi și baze de concentrație slabă	Declared value	Declared value	Declared value	GLA	EN ISO 10545-13
10. Resistance to the high concentration acids and alkalis/ Rezistența la acizi și baze de concentrație mare	Declared value	Declared value	Declared value	GHA	EN ISO 10545-13
11.Stain resistance Rezistența la patare	Min class 3	Min class 3	Min class 5	class 5	EN ISO 10545-14
12. MOHS Rezistența la zgariere	Declared value	Declared value	Declared value	3.5	EN 101:1991

Date: 26.02.2021





**Technical Characteristic KAI/KOS
FISA TEHNICA**

ODU
16.07.05(7/0)

**Model „Celine“
Internal code: 9893
Type Porcelain Tiles GL
Group BIa, Nominal size 333x333 mm**

Characteristics/Caracteristici Group BIa, Annex G	Tolerance EN 14411:2016, %	Tolerance EN14411:2016, mm	Request values/Valori conform standard	Measured in KAI laboratory/Masuratori in laborator Kai	Testing method/Metoda de lucru						
1. Length/width Lungime/Latime, mm	±0.6/max±2mm	±2.00	333x333	<table border="1"> <tr> <td>1C</td> <td>331.0x331.0</td> </tr> <tr> <td>0C</td> <td>333.0x333.0</td> </tr> <tr> <td>2C</td> <td>335.0x335.0</td> </tr> </table>	1C	331.0x331.0	0C	333.0x333.0	2C	335.0x335.0	EN ISO 10545-2
1C	331.0x331.0										
0C	333.0x333.0										
2C	335.0x335.0										
2.Thickness Grosimea, mm	±5/max±0.5mm	±0.40	8.0±0.40mm	7.7 – 7.9 mm	EN ISO 10545-2						
3. Straightness of sides Liniaritatea muchiei,mm	±0.5/max±1.5mm	±1.50	±1.30 mm	-0.14 – +0.23 mm	EN ISO 10545-2						
4. Rectangularity Rectangularitate, mm	±0.5/max±2mm	±1.67	±1.40 mm	0.54 – 0.59 mm	EN ISO 10545-2						
5. Centre curvature Curbura centrala, mm	±0.5/max±2mm	±2.00	±1.50 mm	-0.24 – +0.49 mm	EN ISO 10545-2						
6. Edge curvature Curbura laterala, mm	±0.5/max±2mm	±1.67	±1.40 mm	-0.11– +0.48 mm	EN ISO 10545-2						
7. Warpage Deformarea, mm	±0.5/max±2mm	±2.00	±1.50 mm	-0.39 – +0.43 mm	EN ISO 10545-2						
8. Surface quality Calitatea suprafetei	≥95% without defects	≥95% without defects	≥98% without defects	Pass	EN ISO 10545-2						
9.Water absorption Absorbția de apa, %	≤0,5% Individual ≤0,6%	≤0,5% Individual ≤0,6%	≤0,5%	0.19– 0.27 %	EN ISO 10545-3						
10.Modulus of rupture rezistența mecanică, N/mm ²	≥35N/mm ² individual≥32N/mm ²	≥35N/mm ² individual≥32N/mm ²	≥35N/mm ²	Average: 71 N/mm ²	EN ISO 10545-4						
11. Breaking strength Forța de rupere, N	≥ 1300N	≥ 1300N	≥ 1300N	Average: 1893 N	EN ISO 10545-4						
12.Determination of surface abrasion for glazed tiles/Rezistența la abraziune	the class of abrasive resistance and the number of cycles are declared by producer	the class of abrasive resistance and the number of cycles are declared by producer	Declared value	3/ 750	EN ISO 10545-7						
13.Crazing resistance, glazed tiles/Resistența la crapături pentru plăci glazurate	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant							
14.Resistance for household chemicals and swimming pool salts Rezistența la soluțiile de uz casnic și sărurile de piscină	Min class B	Min class B	Min class B	GA	EN ISO 10545-13						